Critical View® Witness Pro







Mapse Besolution MapSetPoint (SelPS) 1920/1920/1929 1920/1020 PDS) 1920/12010 PDS) 1920/12010 PDS) 1940/2010 PDS) 1940/2010 PDS) Water Funnal Map Nut 1244 11260 Water Funnal Map Nut 1244 11260 Water Funnal Water Adaption 1111 Water Map Water Adaption 1111 Water Mask Water Mask Mater		
vice form B494 with V284 V1285 Like Vices Buppet Vice Apple 64 degrees Wice Apple 64 degrees Vice Apple 64 degrees Hip Outling Muthin Macrophone Ware Mark Barb Outling Muthin Macrophone Ware Mark Barb Outling Free Outling Work Might Muthin Outling Muthin Mut	RECORDING	
Lak Vaco Singert Notorking Anglo War Argle 140 degress Notorking Anglo Hall Castrid Sulleh Miccollones. War Mark Usert D. Ture and date Samp Enredded Hilo Vakes. Soord Mutan TPU Latters. From Castra Valve Warg Main (An edite lique kit er reard) Other Mutan TPU Latters. From Castra Valve Warg Main (An edite lique kit er reard) Other Mutan TPU Latters. From Castra Valve Warg Main (An edite lique kit er reard) Ward Nath Above 15 Souris at 1050° (463VF10*) Ward Nath Sugert Latter (An edite Kit et al.) Ward Nath Sugert Latter (An edite Kit et al.) Ward Nath Sugert Latter (An edite Kit et al.) Ward Nath Sugert Latter (An edite Kit et al.) Ward Nath Sugert Latter (An edite Kit et al.) Ward Nath Sugert Latter (An edite Kit et al.) Ward Nath Datter (Manet Ad.) Ward Nath Datte (An edite Ad.) Ward Natter	Video Resolution	1440P(30FPS)/1296P(30 FPS)/ 1920x1080P(30 FPS)/ 1280x720P(30 FPS)/ 848×480(30 FPS)
Beauding Angle Wide Augle 140 degrees Markin App Calary Bustin Minorphone. Wate Mark Use ILD Trans of Galary Bustin Chreekeds Hito Vatio. Beard Bustin 199 Uniters Print Chrale Valew Big Bustin Chreekeds Hito Vatio. Direr Martin 199 Uniters Print Chrale Valew Big Bustin Chreeke quide to record) Orier Martin 199 Uniters Print Chrale Valew Big Bustin Chreeke quide to record) Wate Databon 100 minor, 20 mino,	Video Format	
Audio High Quality Bullon Margahone. Water Mulan Web Quarter Mulan Endoded MU Veeo. Water Mulan PU Juston. FTT Extons. SQS Yebbe Bullon, Audio Bullon, Ftt Rotton, Laft High I-Continn-Back Bullon Other Station TD Juston. FTT Extons. SQS Yebbe Bullon, Audio Bullon, Fttole Suffor, Power Bullon, IR Button, Laft High I-Continn-Back Bullon Other Station Borgen Zimman, SQ amine Beader Darian Bayont Mulan Darian SQ See Mark LED Indicators HOTOGENEMI Vector & Sgewark ALED Indicators HOTOGENEMI SQ Margahose. SPEG State Brind SQ Margahose. SPEG State State State State State	Live Video	Support
whileMark NameMark NameWater MarkUser D. Three and das Samp Endedded link Webs.Water MarkUser D. Three Mark Samp Endedded link Webs.Water MarkTPU Users. PTT Baters, SSO Yabes Batters, Autos Batters, Paser Batters, IR Batters, IR-R Batter	Recording Angle	Wide Angle 140 degrees
Recod Bullon. TPU bullon. Front Circul at Yellow By Bullon (Ow-elink quelok to neod) Ditle Bullon. TPU bullon. TPT Bullon. SO Yellow Bullon, Audo Bullon, Prover Bullon, Left-Pigglt -Confirm-Back Bullon Web Dutkoon D Yines, 20 min. SO mine Web Dutkoon D Yines, 20 min. SO mine Web Dutkoon D Yines, 20 min. SO mine Web Dutkoon D Yines, 20 mine Web Dutkoon D Yines, 20 mine Web Dutkoon D Yines, 20 mine Web Dutkoon Web So Max & LED Indicators WHOTOBARH Defender Sonth Web Dutkoon D Yines, 20 Magnielis J PEG Singe Shat Capture Printes During Video Recording Type Bullin AufOrnah battery Type Bullin AufOrnah battery Dranging Time D Son induse Weff 2 Addata Bulloch LE 4 Support Holder Higger in D Weff D Sondow Space DBSD DBSD DBSD Bulloch LE 4 Support Holder Or Setting va MCC Orters D Defender Space DBSD DBSD DBSD DBSD DBSD DBSD DBSD DBS	Audio	
Other Buthon 1PU buthon. PTT Buthon. SOB Yaivae Buthon, Nerko Buthon, IR Buthon, LR Huthon, Huthon, LR Huthon, LR Huthon, Huthon, LR Huthon, LR Hut	Water Mark	User ID, Time and date Stamp Embedded into Video.
Video Duration 10 mins, 20 mins, 20 mins Necoding Time Above 15 nois at 1000/ (40XMP1 off) Necoding Time Above 15 nois at 1000/ (40XMP1 off) Necoding Time Support Mathematic Decoding Support Mathematic Decoding Support Strater A Frantal JEG Sames Formal Capture Photos During Video Rocording Strater A Frantal JEG Sames Formal Capture Photos During Video Rocording Strater A Tomal Capture Photos During Video Rocording Strater A Capture Photos During Video Rocording Strater A Capture Photos During Video Rocording Strater A Capture Photos During Video Rocording Strater A Capture Photos During Video Rocording Strater A Capture Photos During Video Rocording Strater A Capture Photos During Video Rocording Strater A Capture Photos During Video Rocording Strater A Capture Photos During Video Rocording Strater A Capture Photos During Video Rocording Strater A Capture Photos During Video Rocording Video Rocording A Capture Photos During Video Rocording Strater A Capture Photos During Video Rocording Video Rocording A Capture Photos During Video Rocording Video Rocording Video Rocording Video Rocording Video Rocording	Record Button	TPU button: Front Circular Yellow Big Button (One-click quick to record)
Recording Time Aloose 16 hours at 1080P (4GA WFF off) Pher Recording Stational Support Advation prompt Water & Support A Phort Constant DPC Stational prompt Water & Support A Phort Constant DPC Statis Station Capture Photos During Video Recording Phort Constant 29 Mageptions and PEC Constant Format 20 Mageptions and PEC Phort Constant 20 Mageptions and PEC Constant Statis Phort 20 Mageptions and PEC Phort Constant 20 Mageptions and PEC Phort Constant 20 Mageptions and PEC Phort Constant 24 Mage Photos During Video Recording Window 24 Mageptions and Phort Constant Water Constant 20 Support Distations and Phort Constant Water Constant 20 Support Constant Support Constant 20 Support Constant Malor Contant 20 Support Constant	Other Button	TPU button: PTT Button, SOS Yellow Button, Audio Button, Photo Button, Power Button, IR Button, Left+Right +Confirm+Back Button
Pre-Rescud/Post Record Support Voltation & Speaker & LED Indicators Voltation (a Speaker & LED Indicators State Format JPEG State Format JPEG State Format State Speaker & LED Indicators Market State Speaker & LED Indicators Pre-Resculture State Speaker & LED Indicators Write Speaker & LED Indicators Speaker & LED Indicators Speaker LED Indicators Speaker & LED Indicators <td>Video Duration</td> <td>10 mins, 20 mins, 30 mins</td>	Video Duration	10 mins, 20 mins, 30 mins
Addition prompt Vitrator & Speaker & LED Indicators PHOTOGRAPH PEG Stage Encards Farmal JEG Stage Encards Farmal Stagepionts JPEG Stage Enclard Stagepionts JPEG Wiff Stage Enclard Stage Enclard Stagepionts JPEG Wiff 240Hz Stage Enclard Stagepionts JPEG Wiff Stage Enclard Stage Enclard LEF=DDD 1698/SMS/SMS202826 Stage Enclard LEF=DDD 1698/SMS/SMS202826 TETDD 2698/SMS201282 LEF DDD 1698/SMS2012825 Stage Enclard LEF=DDD 1698/SMS2012825 Stage Enclard LEF=DD 1698/SMS2012825 Stage Enclard StageAndPate Stage Enclard StageAndPate StageA	Recording Time	Above 15 hours at 1080P (4G&WiFi off)
PHOTOCRAPY PHCS Camera Format JPCG Same Shud Capuire Photo During Welso Recording Photo Resolution 32 Magapiesis JPEG EATTEXY Photo Resolution Symp Sulini -4 400muh ballery Charging Time Sol minute Winites Photo Resolution Sol minute 200 minute Winites Photo Resolution Blandoth BLE 4.0 (Support Hoister trigger and Bluetooth trigger) AG Band LTE-FOOS H393895/7898208283 Strenge Capacity Top Top Strenge Strenger Strenger Active Trigger and Bluetooth trigger) All Band LTE-FOOS H393895/7898208283 Strenge Capacity Top Top Strenge Strenger Strenger Active Trigger and Bluetooth trigger) Viet FOOS H393895/7898208283 Top Top Strenger Active Trigger and Bluetooth trigger) Strenge Capacity Top Top Strenger Active Trigger and Bluetooth trigger) Strenger Capacity Strenger Active Trigger Active	Pre-Record/Post Record	Support
PHOTOCRAPY PHCS Camera Format JPCG Same Shud Capuire Photo During Welso Recording Photo Resolution 32 Magapiesis JPEG EATTEXY Photo Resolution Symp Sulini -4 400muh ballery Charging Time Sol minute Winites Photo Resolution Sol minute 200 minute Winites Photo Resolution Blandoth BLE 4.0 (Support Hoister trigger and Bluetooth trigger) AG Band LTE-FOOS H393895/7898208283 Strenge Capacity Top Top Strenge Strenger Strenger Active Trigger and Bluetooth trigger) All Band LTE-FOOS H393895/7898208283 Strenge Capacity Top Top Strenge Strenger Strenger Active Trigger and Bluetooth trigger) Viet FOOS H393895/7898208283 Top Top Strenger Active Trigger and Bluetooth trigger) Strenge Capacity Top Top Strenger Active Trigger and Bluetooth trigger) Strenger Capacity Strenger Active Trigger Active	Activation prompt	
Shot Caplure Photos During Video Recording Photo Resolution 32 Maganokas JPEG BATTERY Intervideo Control Contector Contro Control Control Contecontrol Control Control Contr	PHOTOGRAPH	
Photo Resolution 32 Megapolesis JPEG EATTERY Extension Stream Extension Type Buil-in 4400mah battery Charging Time 300 minutes Wife 2.4GHz Buttoht BLE 4.0 (Support Hoister trigger and Bluetooth trigger) 46 Band LTE-FDD B1/B3/B5/B7/B8/B20/B28 LTE-FDD S3BM40541 Comport LTE-FDD S3BM40541 VFC Optional / Support to Write ID or Settings via NFC OTHERS Stream Capacity Display Mgh resolution 2inch LCD (480×360 Pusels) Storage Capacity 326/d4Gi1280/25608 Right 292/d580m Right Roll 292/d580m Storage Capacity 326/d4Gi1280/25608 Storage Capacity 326/d4Gi1280/25608 Right 292/d580m Storage Capacity 326/d4Gi1280/25608 Right Roll 292/d580m Storage Capacity 326/d4Gi1280/25608 Right Roll 292/d580m Storage Capacity 326/d4Gi1280/25608 Right Roll 292/d580m Stora	Camera Format	JPEG
Part TERY During Summary Summa	Snap Shot	Capture Photos During Video Recording
BATTERY Builsin 4400mah battery Type Builsin 4400mah battery Charging Time 500 minutes Wirlines 500 minutes Wirlines 2.45Hz Blautoth BLE 4.0. (Support histler fugger and Bluetoch trigger) 4G Band LTE-FDD 3193395/87/88/820828 TE-FDD 3193395/87/88/820828 LTE-FDD 3193395/87/88/820828 TE-FDD 3193395/87/88/820828 LTE-FDD 3193395/87/88/820828 Mire Optional / Support 10 Wite ID or Settings via NFC OTHERS Deploy Might resolution 2nch LCD (480-380 Puels) Storage Capabity 320464/1262/2606B Storage Carboni Support Wite ED Support Storage Carboni Support Storage Carboni	Photo Resolution	
Charging Time 300 minutes Wirkless Wirkless Wirkless 2.4GH2 Blecktoft B.E.4.0 (Support Hotster Virger and Bluetooth tingger) 46 Band LTE-FDD.B.1/BS/B5/B7/B6/B20/B28 LTE-TDD.B.388464/B41 VFC Optional / Support to Write ID or Settings via NFC Display High resolution 2inch LCD (480×380 Pixels) Storage Capacity 32GH46/1/380/256GB Walter Tool Support Storage Capacity 32GH46/1/380/256GB Storage Capacity 32GH46/1/380/256GB Storage Comparity 49G Ad and Blue LED Storage Comparity 49G Ad and Blue LED Autor Ford	BATTERY	
Charging Time 300 minutes Wirkless Wirkless Wirkless 2.4GH2 Blecktoft B.E.4.0 (Support Hotster Virger and Bluetooth tingger) 46 Band LTE-FDD.B.1/BS/B5/B7/B6/B20/B28 LTE-TDD.B.388464/B41 VFC Optional / Support to Write ID or Settings via NFC Display High resolution 2inch LCD (480×380 Pixels) Storage Capacity 32GH46/1/380/256GB Walter Tool Support Storage Capacity 32GH46/1/380/256GB Storage Capacity 32GH46/1/380/256GB Storage Comparity 49G Ad and Blue LED Storage Comparity 49G Ad and Blue LED Autor Ford		Built-in 4400mah battery
Winkless Control Winition 2.4GHz Bluetooth BLE 4.0 (Support Hotster trigger and Bluetooth trigger) 4G Band ELF-DDB BINBASBY 7/BB/B2/08/28 4G Band ELF-DDB BINBASBY 7/BB/B2/08/28 VEC Optional / Support to Write ID or Sattings via NFC OTHERS Delonal / Support to Write ID or Sattings via NFC OTHERS 200640/126/25608 Bluetooth 200640/126/25608 RI Light 2PCS Boom Large Infrared LED Auto IR Control Support Wite EDD Support Wite EDD Support Wite FDD Support Support Support Wite FDD Support Wite FDD Support Support Support Support Support Support Support Support Support Support Support <td>Charging Time</td> <td></td>	Charging Time	
Bluetoth BLE 4.0 (Support Holster trigger and Bluetoth trigger) HG Band LTE-FDD B1/B3/B5/67/B8/B2/08/28 LTE-FDD B3/B4/0F41 Choose 2000 NFC Optional / Support to Write ID or Settings via NFC OTHER Display Bill resolution 2inch LCD (480-380 Pixels) Control Storage Capacity 2G/64G/12G/256GB RI Light 2PCS 860mL arge Infrared LED Auto IR Control Support Nife LED Support Storage Capacity Support SQ EAD Red and Blue LED SQ EAD Red and Blue LED SQ EAD High Coulding Metal Clip with 380° Rotation Materpoord IPG Clip High Coulding Metal Clip with 380° Rotation Magnetic Connector Support 3.5mm Earphone Password Protocton Support 3.5mm Earphone Dimensions 85-68-27.9mm Weight 155 Grams Working Temperature -200° - 650° Vorkes Enorption Support ASSS6 GPS GPS GPS GPS	Wireless	
AG Band LTE-FDD.81/83/85/87/88/B2082a 4G Band LTE-FDD.81/83/85/87/88/B2082a LTE-TDD.83/85/87/88/B2082a LTE-TDD.83/85/87/88/B2082a VFC Optional / Support to Write ID or Settings via NFC OTHERS Image: Comparison of	WiFi	2.4GHz
AG Band LTE-FDD.B1/B3/B5/B7/B8/B20/B28 LTE-FDD.B3/B40/B41 NFC Optional / Support to Write D or Settings via NFC OTHERS Image: Comparity Display High resolution 2inch LCD (480-380 Poxels) Storage Capacity 32G/64G/128G/256GB RL Ught 2PCS 850mm Large Infrared LED Auto IR Control Support White LED Support SoS LED Red and Bite LED Spacker Waterproof and High-power Speaker Waterproof IP67 Clip High Quality Metal Clip with 380° Rotation Magnetic Connector Support Autol R Control Support 3.5mm Earphone Password Protecton Requires Password to Access to Video Dimensions 86-56.6.27.9mm Weight 155 Grams Working Temperature -20C° - 65C° Storage Interperature -20C° - 65C° G PS GPS GA Software Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) Accessories Magnetic USB cable, Charger, Single Dock, Crocodie Clip, Klickfast, Manual <	Bluetooth	BLE 4.0 (Support Holster trigger and Bluetooth trigger)
IT=TDD B38P40/B41 VPC 0 Option / Support to Wite ID or Settings via NPC OTHERS C Objeky High resolution 2inch LCD (480×380 Pixels) Storage Capacity SGr64/128G/256G8 RL ught 2Gr64 S01xm Large Infrared LED Auto IR Control Support Storage Capacity Support Storage Capacity Support Storage Capacity Support Auto IR Control Support Storage Capacity Support Support Support Support Support Clip High Quality Metal Clip with S00* Rotation Support Support Support Support Support Support Support Support Support Support Support Support Support Support Support Support Support Support Support Support Support Support Support Support Support Support Support Support	4G Band	
OTHERS High resolution 2inch LCD (480×360 Pixels) Display High resolution 2inch LCD (480×360 Pixels) Storage Capacity 32G/64G/128G/266GB IR Light 2PCS 850m Large Infrared LED Auto IR Control Support Storage Capacity Support SoS LED Red and Blue LED Speaker Waterproof and High-power Speaker Waterproof IP67 Clip High Quality Metal Clip with 360° Rotation Magnetic Connector Support Support 3.5mm Earphone Password Protection Password Protection Reguines Password to Access to Video Dimensions 85-56.8-27.9mm Weight 155 Grams Working Temperature -20C° - 65C° Video Encryption Support AES256 GPS GPS GA Software Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual		LTE-TDD:B38/B40/B41
Display High resolution 2inch LCD (480×360 Pixels) Storage Capacity 32G/64G/128G/256GB IR Light 2PCS 850nm Large Infrared LED Auto IR Control Support Storage Capacity Waterpoor Speaker Waterpoor and High-power Speaker Waterpoor IP67 Clip High Quality Metal Clip with 360° Rotation Magnetic Connector Support Auto - in/out Support 3.5mm Earphone Password Protection Requires Password to Access to Video Dimensions Storage Target Sci	NFC	Optional / Support to Write ID or Settings via NFC
Storage Capacity 320/64G/128G/256GB IR Light 2PCS 850nn Large Infrared LED Auto IR Control Support Storage Capacity Support Waterproof Waterproof and High-power Speaker Waterproof Pfo7 Clip High Quality Metal Clip with 360° Rotation Magnetic Connector Support Auto -in/out Support Subport 3.5mm Earphone Support Verklip Temperature Suport - 65C° Working Temperature 20C° - 65C° Working Temperature 20C° - 65C° Videe Encryption Support AES256 GPS GPS 4S oftware Platform CMSV (Real Time Monitoring/ SOS/ GPS Tr	OTHERS	
IR Light 2PCS 850nm Large Infrared LED Auto IR Control Support White LED Support SOS LED Red and Blue LED Speaker Waterproof and High-power Speaker Waterproof IP67 Clip High Quality Metal Clip with 360° Rotation Magnetic Connector Support Auto In/out Support 3.5mm Earphone Password Protection Requires Password to Access to Video Dimensions 85×66.8×27.9mm Weight 155 Grams Working Temperature -200° ~ 65C° Storage temperature -200° ~ 65C° QRS GPS GPS GPS AGS oftware Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Standard Accessories	Display	High resolution 2inch LCD (480×360 Pixels)
Auto IR Control Support White LED Support SOS LED Red and Blue LED Speaker Waterproof and High-power Speaker Waterproof IP67 Clip High Quality Metal Clip with 360° Rotation Magnetic Connector Support Autio Air/out Support 3.5mm Earphone Password Protection Requires Password to Access to Video Dimensions 85×66.8×27.9mm Weight 155 Grams Working Temperature -200° ~ 650° Storage temperature -200° ~ 650° GPS GPS 4G Software Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	Storage Capacity	32G/64G/128G/256GB
White LED Support SOS LED Red and Blue LED Speaker Waterproof and High-power Speaker Waterproof IP67 Clip High Quality Metal Clip with 360° Rotation Magnetic Connector Support Auido -In/out Support 3.5mm Earphone Password Protection Requires Password to Access to Video Dimensions 85×6.8×27.9mm Weight 155 Grams Working Temperature -20°° ~ 65°° Storage temperature -20°° ~ 65°° GPS GPS GPS GPS GS oftware Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	IR Light	2PCS 850nm Large Infrared LED
SOS LED Red and Blue LED Speaker Waterproof and High-power Speaker Waterproof IP67 Clip High Quality Metal Clip with 360° Rotation Magnetic Connector Support Auido -in/out Support 3.5mm Earphone Password Protection Requires Password to Access to Video Dimensions B5×56.8×27.9mm Weight 155 Grams Working Temperature -200° ~ 650° Video Encryption Support AES256 GPS GPS 4G Software Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Standard Accessories	Auto IR Control	Support
Speaker Waterproof and High-power Speaker Waterproof IP67 Clip High Quality Metal Clip with 360° Rotation Magnetic Connector Support Auido -in/out Support 3.5mm Earphone Password Protection Requires Password to Access to Video Dimensions 85×56.8×27.9mm Weight 155 Grams Working Temperature -20C° ~ 65C° Storage temperature -20C° ~ 65C° Video Encryption Support AES256 GPS GPS 42 Software Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	White LED	Support
Waterproof IP67 Clip High Quality Metal Clip with 360° Rotation Magnetic Connector Support Auido -in/out Support 3.5mm Earphone Password Protection Requires Password to Access to Video Dimensions 85×56.8×27.9mm Weight 155 Grams Vorking Temperature -20C° ~ 65C° Storage temperature -20C° ~ 65C° Video Encryption Support AES256 GPS GPS 4S oftware Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	SOS LED	Red and Blue LED
Clip High Quality Metal Clip with 360° Rotation Magnetic Connector Support Auido -in/out Support 3.5mm Earphone Password Protection Requires Password to Access to Video Dimensions 85×56.8×27.9mm Weight 155 Grams Working Temperature -200° ~ 650° Storage temperature -200° ~ 650° Video Encryption Support AES256 GPS GPS GS Software Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	Speaker	Waterproof and High-power Speaker
Magnetic Connector Support Auido -in/out Support 3.5mm Earphone Password Protection Requires Password to Access to Video Dimensions 85×56.8×27.9mm Weight 155 Grams Working Temperature -200° ~ 650° Storage temperature -200° ~ 650° Video Encryption Support AES256 GPS GPS 4G Software Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) Accessories Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	Waterproof	IP67
Auido -in/out Support 3.5mm Earphone Password Protection Requires Password to Access to Video Dimensions 85×56.8×27.9mm Weight 155 Grams Working Temperature -20C° ~ 65C° Storage temperature -20C° ~ 65C° Video Encryption Support AES256 GPS GPS 4G Software Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	Clip	High Quality Metal Clip with 360° Rotation
Password Protection Requires Password to Access to Video Dimensions 85×56.8×27.9mm Weight 155 Grams Working Temperature -20C° ~ 65C° Storage temperature -20C° ~ 65C° Video Encryption Support AES256 GPS GPS 4G Software Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	Magnetic Connector	Support
Dimensions 85×56.8×27.9mm Weight 155 Grams Working Temperature -20C° ~ 65C° Storage temperature -20C° ~ 65C° Video Encryption Support AES256 GPS GPS 4G Software Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Jandard Accessories Standard Accessories Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	Auido -in/out	Support 3.5mm Earphone
Weight 155 Grams Working Temperature -20C° ~ 65C° Storage temperature -20C° ~ 65C° Video Encryption Support AES256 GPS GPS 4G Software Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	Password Protection	Requires Password to Access to Video
Working Temperature -20C° ~ 65C° Storage temperature -20C° ~ 65C° Video Encryption Support AES256 GPS GPS 4G Software Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Standard Accessories Standard Accessories Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	Dimensions	85×56.8×27.9mm
-20C° ~ 65C° Storage temperature -20C° ~ 65C° Video Encryption Support AES256 GPS GPS 4G Software Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Standard Accessories Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	Weight	155 Grams
Video Encryption Support AES256 GPS GPS 4G Software Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Standard Accessories Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	Working Temperature	-20C° ~ 65C°
GPS GPS 4G Software Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Standard Accessories Standard Accessories Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	Storage temperature	-20C° ~ 65C°
AG Software Platform CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom) ACCESSORIES Standard Accessories Standard Accessories Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	Video Encryption	Support AES256
ACCESSORIES Standard Accessories Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	GPS	GPS
Standard Accessories Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual	4G Software Platform	CMSV (Real Time Monitoring/ SOS/ GPS Tracking/ Intercom)
	ACCESSORIES	
Other Accessories Magnet Mount, Lock Clip, Car Mount, Harness, Earphone, Bluetooth holster sensor	Standard Accessories	Magnetic USB cable, Charger, Single Dock, Crocodile Clip, Klickfast, Manual
	Other Accessories	Magnet Mount, Lock Clip, Car Mount, Harness, Earphone, Bluetooth holster sensor